

## TriTech Airless

# TriTech.

Τ7

**2.91** Itrs/min

**0.027"** Max tip

#### Use to spray

Emulsion, interior and exterior
Water or solvent based top coats
Wood preservatives
Most other
medium-viscosity water or solvent based coatings



**✓** Decorative

**✓** Industrial

✓ Flat out 24/7

#### **Product Codes**

110 volt 600-853 240 volt 600-844

### **Complete with**

TriTech T380 Contractor spray

TriTech Contractor 517 airless tip TriTech Contractor safety guard 1/4" x 15m textile hose assembly QLube x 237ml piston lubricant

### **Specification**

Flow 2.91 ltr/min Max tip 0.027" MWP 227 bar | 3300 psi Motor 1195 watt PMDC Weight 34.9 kg Power supply 110 / 240 volt

#### **Features**

Designed, engineered and built - all in the USA Aerospace grade materials used throughout

High grade aluminium for the control box, motor cover and heat sink - aluminium dissipates heat, as opposed to plastic which retains it

Steel cut and precision ground gears - running in synthetic grease for positive heat transfer

Frame from chrome plated heavy walled steel tubing, immensely strong and tough

TriTech proprietary carbide blend is used for the ball and seat to give a superior and positive shut off All covered by the unique TriTech warranty